

**Material Safety Data Sheet**  
**Not Classified as Hazardous According to the Criteria of Worksafe Australia**

**IDENTIFICATION**

Product name: **ATELIER MODELLING COMPOUND** U.N. No: **N/A**  
Other names: **----** Hazchem: **N/A**  
Dangerous Goods Class & Sub Risk: **N/A**  
Manufacturer's Product Code: **VARIOUS** Poisons Schedule: **N/A**  
Use: **FOR TEXTURAL EFFECTS WITH ARTISTS PAINT**

**Physical Description/Properties**

Appearance: **CREAMY WHITE PASTE** Flash Point (°C): **N/A**  
Boiling Point/Melting Point (°C) **N/A** Flammability limits (%): **N/A**  
Vapour Pressure (pascals or mm of Hg at 25°C) **N/A** Solubility in Water (g/L): **soluble**  
Specific Gravity **APPROX 1.15g/ml**  
Other properties **Slight ammonia smell**  
Ingredients

Chemical entity	CAS No.	Proportion
<b>ACRYLIC EMULSION</b>	<b>NON HAZ</b>	<b>COMMERCIAL IN CONFIDENCE</b>
<b>AMMONIA</b>	<b>7-664-41-7</b>	<b>&lt;0.2%</b>
<b>PRESERVATIVE</b>	<b>149-30-4/2634-33-5</b>	<b>0.3%</b>
<b>WATER</b>	<b>7732-18-5</b>	<b>COMMERCIAL IN CONFIDENCE</b>

**HEALTH HAZARD INFORMATION**

**HEALTH EFFECTS:**

**Acute:** Swallowed **NONE ALLOCATED**  
Eye **DIRECT CONTACT MAY CAUSE SLIGHT IRRITATION**  
Skin **PROLONGED OR REPEATED CONTACT MAY CAUSE SLIGHT SKIN IRRITATION**  
Inhaled **INHALATION OF VAPOUR MAY CAUSE IRRITATION**

**Chronic** **NONE ALLOCATED**

**FIRST AID:**

Swallowed **IF SWALLOWED GIVE TWO GLASSES OF WATER TO DRINK**  
Eye **FLUSH EYES WITH A LARGE AMOUNT OF WATER**  
Skin **WASH AFFECTED SKIN AREAS THOROUGHLY**  
Inhaled **MOVE SUBJECT TO FRESH AIR**

**ADVICE TO DOCTOR** **THIS PRODUCT CARRIES THE C.P. NON-TOXIC SEAL AND IS CERTIFIED BY A TOXICOLOGIST IN ASSOCIATION WITH THE ART & CRAFT MATERIALS INSTITUTE, BOSTON Ma 02110 USA.**

**PRECAUTIONS FOR USE****EXPOSURE STANDARDS**

NONE

**ENGINEERING CONTROLS**

USE IN WELL VENTILATED AREAS

**PERSONAL PROTECTION**

NONE REQUIRED IF USED IN A WELL VENTILATED AREA

**FLAMMABILITY**

N/A

**SAFE HANDLING INFORMATION****STORAGE & TRANSPORT**

KEEP FROM FREEZING. RECOMMENDED STORAGE CONDITIONS ARE BETWEEN 1° C AND 50 °C.

**SPILLS & DISPOSAL**

FOR LARGER QUANTITIES, CONTAIN ANY SPILLS WITH INERT MATERIALS, (SAND, SAWDUST ETC) AND TRANSFER TO CONTAINERS FOR DISPOSAL. CONTACT LOCAL WASTE DISPOSAL AUTHORITY FOR DISPOSAL METHODS. SOAK UP SMALLER SPILLS WITH A RAG AND DISPOSE OF CAREFULLY.

**FIRE/EXPLOSION HAZARD**

NONE

**OTHER INFORMATION****CONTACT POINT**

MT KURING-GAI AUSTRALIA

**DATE OF ISSUE: 1 SEPTEMBER 2006**