

CHROMA AUSTRALIA PTY LTD ACN 001 594 609
17 MUNDOWI RD
MT KURING-GAI NSW 2080, Australia
TEL: (02) 9457 9922 FAX: (02) 9457 8082
EMERGENCY TEL: AS ABOVE, or POISONS INFORMATION CENTRE

PAGE 1 of 2

DATE of ISSUE: 1 SEPTEMBER 2006

Material Safety Data Sheet
Not Classified as Hazardous According to the Criteria of Worksafe Australia

IDENTIFICATION

Product name: **Atelier Satin Painting Medium & Varnish** U.N. No: **N/A**
Other names: ---- Hazchem: **N/A**
Dangerous Goods Class & Sub Risk: **N/A**
Manufacturer's Product Code: **AT72600** Poisons Schedule: **N/A**
Use: Satin water based varnish and medium for artists' acrylic paints

Physical Description/Properties

Appearance: Milky Liquid Flash Point (°C): **> N/A**
Boiling Point/Melting Point (°C) **N/A** Flammability limits (%): **N/A**
Vapour Pressure (pascals or mm of Hg at 25°C) **N/A** Solubility in Water (g/L): **Soluble**
Specific Gravity **APPROX 1 g/ml**
Other properties

Ingredients

Chemical entity	CAS No.	Proportion
ACRYLIC EMULSION	NON HAZARDOUS	COMMERCIAL IN CONFIDENCE
AMMONIA	7-664-44-7	<2%
PRESERVATIVE	149-30-4/2634-33-5	0.2%
WATER	7732-15-5	COMMERCIAL IN CONFIDENCE
THICKENERS	NON HAZARDOUS	5%

HEALTH HAZARD INFORMATION

HEALTH EFFECTS:

Acute: **Swallowed** NONE ALLOCATED
Eye DIRECT CONTACT MAY CAUSE SLIGHT IRRITATION
Skin PROLONGED OR REPEATED CONTACT MAY CAUSE SLIGHT SKIN IRRITATION
Inhaled INHALATION OF VAPOUR MAY CAUSE IRRITATION
Chronic NONE ALLOCATED

FIRST AID:

Swallowed IF SWALLOWED GIVE TWO GLASSES OF WATER TO DRINK
Eye FLUSH EYES WITH A LARGE AMOUNT OF WATER
Skin WASH AFFECTED SKIN AREAS THOROUGHLY
Inhaled MOVE SUBJECT TO FRESH AIR

ADVICE TO DOCTOR:

THIS PRODUCT CARRIES THE C.P. NON-TOXIC SEAL AND IS CERTIFIED BY A TOXICOLOGIST IN ASSOCIATION WITH THE ART & CRAFT MATERIALS INSTITUTE, BOSTON, MA 02110 USA.

PRECAUTIONS FOR USE**EXPOSURE STANDARDS**

NONE

ENGINEERING CONTROLS

USE IN WELL VENTILATED AREAS

PERSONAL PROTECTION

NONE REQUIRED IF USED IN A WELL VENTILATED AREA

FLAMMABILITY

N/A

SAFE HANDLING INFORMATION**STORAGE & TRANSPORT**

KEEP FROM FREEZING. RECOMMENED STORAGE CONDITIONS ARE BETWEEN 1°C AND 50°C .

SPILLS & DISPOSAL

FOR LARGER QUANTITIES, CONTAIN ANY SPILLS WITH INERT MATERIAL S, (SAND, SAWDUST ETC) AND TRANSFER CONTAINERS FOR DISPOSAL . CONTACT LOCAL WASTE DISPOSAL AUTHORITY FOR DISPOSAL METHODS. SOAK UP SMALLER SPILLS WITH A RAG AND DISPOSE OF CAREFULLY.

FIRE/EXPLOSION HAZARD

NONE

OTHER INFORMATION**CONTACT POINT:**

MT KURING-GAI N.S.W.

DATE OF ISSUE: 1 SEPTEMBER 2006