

Material Safety Data Sheet

ATELIER UNLOCKING FORMULA

Identity (Trade Name As Used On Label)

CHROMA INC
 Manufacturer
 205 BUCKY DRIVE
 Address
 LITITZ PA 17543
 (717)626-8866
 Phone Number (For Information)
 (717)626-8866
 Emergency Phone Number Telex*

MSDS Number*
 CAS Number*
 06/09
 Date Prepared
 Prepared By*
 Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION

COMPONENTS — Chemical Name & Common Names (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)	%*	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED
CONTAINS:				
ISOPROPYL ALCOHOL				CAS: 67-63-0
RESIN				CAS: 2530-83-8
WATER				
FLAMMABLE 3 UNI219, II				
Non-Hazardous Ingredients				
TOTAL	100			

SECTION 2 - PHYSICAL / CHEMICAL CHARACTERISTICS

Boiling Point	180° - 181°F	Specific Gravity (H ₂ O = 1)	.79@68
Vapor Pressure (mm Hg and Temperature)	96 AT 100°F	Melting Point	N/A
Vapor Density (Air = 1)	N/A	Evaporation Rate	2.3 = 1)
Solubility in Water	100.00 AT 68°F	Water Reactive	
Appearance and Odor	CLEAR COLORLESS LIQUID, STRONG ODOR		

SECTION 3 - FIRE AND EXPLOSION HAZARD DATA

Flash Point and Method Used	53°F TCC	Auto-Ignition Temperature	662°F	Flammability Limits in Air % by Volume	2.0	LEL	UEL	12.7
Extinguisher Media	WATER, FOAM, OR DRY CHEMICAL							
Special Fire Fighting Procedures	AS ABOVE							
Unusual Fire and Explosion Hazards	NONE							

*Optional

SECTION 4 - REACTIVITY HAZARD DATA PAGE 2 - ATELIER UNLOCKING FORMULA**STABILITY** Stable
 UnstableConditions
To Avoid

N/A

Incompatibility
(Materials to Avoid)

CAUSTICS, AMINES, ALKANOLA MINES, ALDEHYDES, STRONG OXIDIZING AGENTS AND

Hazardous
Decomposition Products

CHLORINATED COMPOUNDS

HAZARDOUS POLYMERIZATION May Occur
 Will Not OccurConditions
To Avoid

N/A

SECTION 5 - HEALTH HAZARD DATA**PRIMARY ROUTES
OF ENTRY** Inhalation
 Skin Absorption
 Ingestion
 Not Hazardous**CARCINOGEN
LISTED IN** NTP
 IARC Monograph
 OSHA
 Not Listed**HEALTH HAZARDS**

Acute PROLONGED OR REPEATED CONTACT WITH SKIN MAY IRRITATE AND CAUSE

Chronic DERMATITIS, HIGH VAPOR CONCENTRATIONS ARE IRRITATING TO THE EYE AND

Signs and Symptoms
of Exposure

RESPIRATORY TRACT. MAY CAUSE HEADACHES AND DIZZINESS MAY HAVE OTHER

Medical Conditions
Generally Aggravated by Exposure

DERMATITIS

CENTAL NERVOUS EFFECTS.

EMERGENCY FIRST AID PROCEDURES - Seek medical assistance for further treatment, observation and support if necessary.

Eye Contact

IMMEDIATELY FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES

Skin Contact

IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER, USE SOAP IF AVAILABLE
REMOVE CONTAMINATED CLOTHING.

Inhalation

IMMEDIATELY REMOVE THE AFFECTED VICTIM FROM EXPOSURE.

Ingestion

IF SWALLOWED DO NOT INDUCE VOMITING. KEEP AT REST AND GET PROMPT MEDICAL
ATTENTION**SECTION 6 - CONTROL AND PROTECTIVE MEASURES**Respiratory Protection
(Specify Type)

NOT REQUIRED UNDER NORMAL USE

Protective Gloves

NOT REQUIRED UNDER NORMAL USE

Eye Protection

NOT REQUIRED UNDER NORMAL USE

**VENTILATION
TO BE USED** Local Exhaust Mechanical (general) Special Other (specify)

USE IN VENTILATED AREA

Other Protective
Clothing and Equipment

NOT REQUIRED UNDER NORMAL USE

Hygienic Work
Practices

AVOID SKIN CONTACT AND PROLONGED OR REPEATED INHALATION

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE / LEAK PROCEDURESSteps to be Taken If Material
Is Spilled Or ReleasedREMOVE ALL IGNITION SOURCES, DIKE WITH VERY ABSORBENT MATERIAL AND
SAND, EARTH, SAWDUST, ETC. UNIT RATE CONFINED SPACES. KEEP OUT OFWaste Disposal
MethodsSEWER AND WATERWAYS.
CONTACT LOCAL WASTE MANAGEMENT AUTHORITYPrecautions to be Taken
in Handling and Storage

DO NOT STORE NEAR HEAT, SPARK, OR FLAME.

Other Precautions and/or Special Hazards

AVOID SKIN CONTACT AND PROLONGED OR REPEATED INHALATION

NFPA

Rating* Health ___ Flammability ___ Reactivity ___ Special ___

HMIS

Rating* Health 2 Flammability 3 Reactivity 0 Personal Protection ___