

CHROMA AUSTRALIA PTY LTD ACN 001 594 609
17 MUNDOWI RD
MT KURING-GAI NSW 2080, Australia
TEL: (02) 9457 9922 FAX: (02) 9457 8082
EMERGENCY TEL: AS ABOVE, or Poisons Information Centre

PAGE 1 of 2

DATE of ISSUE: 19 October 2000

Material Safety Data Sheet
Classified as Hazardous According to the Criteria of Worksafe Australia

IDENTIFICATION

Product name **CHROMA GLOSS SOLVENT VARNISH** U.N. No: **1300**
Other names: ---- Hazchem: **3Y**
Dangerous Goods Class & Sub Risk: **3.2**
Manufacturer's Product Code: **various** Poisons Schedule: **S5**
Use: **SOLVENT STRIPPABLE ARTISTS' FINISHING VARNISH**

Physical Description/Properties

Appearance: **CLEAR LIQUID** Flash Point (°C): **36°C**
Boiling Point/Melting Point (°C) **146°C** Flammability limits (%): **N/A**
Vapour Pressure (pascals or mm of Hg at 25°C) **N/A** Solubility in Water (g/L): **Insoluble**
Specific Gravity **APPROX 0.85 – 0.9g/mL**
Other properties

Ingredients

Chemical entity	CAS No.	Proportion
ACRYLATE COPOLYMER	COMMERCIAL IN CONFIDENCE	48%
MINERAL TURPENTINE	64742-95-6	50%
PRESERVATIVE	62530-20-1	2%

HEALTH HAZARD INFORMATION

HEALTH EFFECTS:

Acute: Swallowed Moderately toxic. May cause gastric irritation , nausea/vomiting & abdominal pain.
Eye Moderate irritation
Skin Repeated or prolonged contact may lead to dermatatic effects.
Inhaled May be harmful. May cause irritation to the nose and throat.

Chronic Vapours can cause headache, dizziness and possible naausea. Effects of exposure are cumulative. Prolonged skin contact can cause chronic dermatitis.

FIRST AID:

Swallowed Rinse mouth thoroughly with water. Give water to drink. **DO NOT INDUCE VOMITING.** Seek medical attention.
Eye Rinse eyes thoroughly for at least 15 minutes.
Skin Wash skin with soap and water.
Inhaled Remove patient from affected area to fresh air.

ADVICE TO DOCTOR

TREAT SYMPTOMATICALLY

PRECAUTIONS FOR USE**EXPOSURE STANDARDS**

Inhalation TCLo (human): 600mg/m³ /8H: 1RR (based on petroleum spirits. TLV/TWA 480gm/m³.

Guidelines for good practice: Atmospheric contamination should be kept to as low a level as possible.

ENGINEERING CONTROLS

To maintain levels below the recommended exposure limit, product must be used in well ventilated room/area.

PERSONAL PROTECTION

Safety glasses or face shield, gloves and apron

FLAMMABILITY

Avoid ALL ignition sources

SAFE HANDLING INFORMATION**STORAGE & TRANSPORT**

STORE IN A COOL PLACE AWAY FROM HEAT SOURCES OR IGNITION.

SPILLS & DISPOSAL

REMOVE ALL POSSIBLE SOURCES OF IGNITION. USE ABSORBENT MATERIALS - SAND OR SOIL, SAWDUST ETC. TO CONTAIN SPILL. PLACE IN APPROPRIATELY LABELLED CONTAINER FOR SAFE DISPOSAL . CONTACT LOCAL WASTE DISPOSAL AUTHORITY FOR DISPOSAL METHODS.

FIRE/EXPLOSION HAZARD

CARBON MONOXIDE. EXTINGUISH FIRES WITH: CO₂, DRY CHEMICAL OR FOAM.

OTHER INFORMATION

DO NOT STORE WITH STRONG OXIDANTS, SUCH AS LIQUID CHLORINE AND SODIUM HYPOCHLORITE.

CONTACT POINT

MT KURING-GAI AUSTRALIA

DATE OF ISSUE: 4TH NOVEMBER, 2003