

CHROMA AUSTRALIA PTY LTD ACN 001 594 609
17 MUNDOWI RD
MT KURING-GAI NSW 2080, Australia
TEL: (02) 9457 9922 FAX: (02) 9457 8082
EMERGENCY TEL: AS ABOVE, or POISONS INFORMATION CENTRE

PAGE 1 of 2

DATE of ISSUE: 1 SEPTEMBER 2009

Material Safety Data Sheet

Not Classified as Hazardous According to the Criteria of Worksafe Australia

IDENTIFICATION

Product name: **ATELIER FAST MEDIUM / FIXER** U.N. No: **N/A**
Other names: **---** Hazchem: **N/A**
Dangerous Goods Class & Sub Risk: **N/A**
Manufacturer's Product Code: **Various** Poisons Schedule: **N/A**

Use: To fix layers of Interactive paint fast, especially when wanting to achieve multiple layers of glazing.
Speeds drying time.

Physical Description/Properties

Appearance: **WHITE LIQUID** Flash Point (°C): **N/A**
Boiling Point/Melting Point (°C) **N/A** Flammability limits (%): **N/A**
Vapour Pressure (pascals or mm of Hg at 25°C) **N/A** Solubility in Water (g/L): **soluble**
Specific Gravity **APPROX 1 g/ml**
Other properties

Ingredients

Chemical entity	CAS No.	Proportion
ACRYLIC EMULSION	NON HAZ	COMMERCIAL IN CONFIDENCE
AMMONIA	7-664-41-7	0.5%
PRESERVATIVES	149-30-4 / 2634-33-5	0.15%
WATER	7732-18-5	10% - 15%

HEALTH HAZARD INFORMATION

HEALTH EFFECTS:

Acute: Swallowed **NONE ALLOCATED**
Eye **DIRECT CONTACT MAY CAUSE SLIGHT IRRITATION**
Skin **PROLONGED OR REPEATED CONTACT MAY CAUSE SLIGHT SKIN IRRITATION**
Inhaled **INHALATION OF VAPOUR MAY CAUSE IRRITATION**
Chronic **NONE ALLOCATED**

FIRST AID:

Swallowed **IF SWALLOWED GIVE TWO GLASSES OF WATER TO DRINK**
Eye **FLUSH EYES WITH A LARGE AMOUNT OF WATER**
Skin **WASH AFFECTED SKIN AREAS THOROUGHLY**
Inhaled **MOVE SUBJECT TO FRESH AIR**

ADVICE TO DOCTOR

THIS PRODUCE CARRIES THE C.P. NON-TOXIC SEAL AND IS CERTIFIED BY A TOXICOLOGIST IN ASSOCIATION WITH THE ART & CRAFT MATERIALS INSTITUTE, BOSTON Ma 02110 USA.

PRECAUTIONS FOR USE**EXPOSURE STANDARDS**

NONE

ENGINEERING CONTROLS

USE IN WELL VENTILATED AREAS

PERSONAL PROTECTION

NONE REQUIRED IF USED IN A WELL VENTILATED AREA

FLAMMABILITY

N/A

SAFE HANDLING INFORMATION**STORAGE & TRANSPORT**

KEEP FROM FREEZING. RECOMMENDED STORAGE CONDITIONS ARE BETWEEN 1° C AND 50 °C.

SPILLS & DISPOSAL

FOR LARGER QUANTITIES, CONTAIN ANY SPILLS WITH INERT MATERIALS, (SAND, SAWDUST ETC) AND TRANSFER TO CONTAINERS FOR DISPOSAL. CONTACT LOCAL WASTE DISPOSAL AUTHORITY FOR DISPOSAL METHODS. SOAK UP SMALLER SPILLS WITH A RAG AND DISPOSE OF CAREFULLY.

FIRE/EXPLOSION HAZARD

NONE

OTHER INFORMATION**CONTACT POINT**

MT KURING-GAI AUSTRALIA

DATE OF ISSUE: 1 SEPTEMBER 2009