

# CHROMA'S JO SONJA®

## FACT SHEET

### ALL PURPOSE SEALER

Pure Acrylic Binder which can be used on its own or mixed 1:1 with a Jo Sonja's Artists' Colour to seal and promote better adhesion.

Especially recommended to prevent paint moisture loss into very porous surfaces.

May be mixed with JO SONJA Tube and Background Colours.

#### **WOOD PIECES:**

Can be sealed with All Purpose Sealer. Apply undiluted. If you wish to thin the All Purpose Sealer, use 1 part Flow Medium to 2 parts All Purpose Sealer. Do not dilute the All Purpose Sealer with water or Retarder Medium as this would tend to raise the wood grain. Apply using a soft brush or sponge. Sand when dry and proceed to paint. You may sand and/or paint even if the surface feels slightly tacky.

#### **SHINY TIN OR METAL:**

These surfaces should be scuffed with fine grit sandpaper or buffed thoroughly with an abrasive cleansing powder such as "COMET" cleanser. The objective is to provide a "tooth" to the surface for proper adhesion. The surface should be clean and free from all dirt and rust. Applying an water based anti rust metal primer is recommended prior to applying All Purpose Sealer.

Apply All Purpose Sealer undiluted using a sponge or soft fibred brush. Proceed to base paint and/or decorate as soon as dry enough to handle without damaging the surface. Depending on climatic conditions, this could be as soon as two hours.

#### **DRYING TIMES:**

May be shortened by blowing hot air over the surface of your piece with a hair drier set on low. Allow piece to cool to room temperature before proceeding to next steps.

#### **REMEMBER:**

**Maximum adhesion develops over time. This varies with climatic conditions, so allow yourself sufficient time to evaluate your results.**